



## LCD projector

### PT-VX510

- **Brightness: 5500 lumens**
- **1.6X zoom lens**
- **10W speaker and microphone input to enable audio playback**
- **Brightness: 5500 lumens**
- **Contract ratio: 3500:1**
- **0.63" 4:3 (x3) LCD panel**
- **Resolution: 1024 x 768 (True XGA)**
- **1.6X zoom lens**
- **HDMI/S-Video/Video/ RGB/Audio in**

#### General

<b>Panel Type</b>	<b>0.63" LCD x 3</b>
<b>Lamp</b>	<b>280W x 1</b>
<b>Brightness</b>	<b>5500 lumens</b>
<b>Lens</b>	<b>F1.60-2.12, f15.28-24.62mm</b>
<b>Contrast (Full on / Full off)</b>	<b>3500:1</b>
<b>Resolution (Native / maximum)</b>	<b>XGA</b>
<b>H-Sync/V-Sync Range</b>	<b>RGB: 15-100 kHz / 50-100 Hz</b>
<b>Video Compatibility</b>	<b>PAL, PAL-M, PAL-N, PAL60, SECAM, NTSC, NTSC4.43</b>
<b>Screen Size</b>	<b>30" - 300"</b>
<b>Lens Shift</b>	<b>Vertical +40°</b>
<b>Keystone Correction Range</b>	<b>Vertical ±30° (±20° when auto mode)</b>
<b>Weight</b>	<b>Approx 4.8kg</b>
<b>Dimensions (W x H x D)</b>	<b>379 x 107 x 305 mm</b>
<b>Power Consumption</b>	<b>365W (Standby mode : 0.3W(eco), 11.5W(network))</b>
<b>Terminals</b>	<b>PC Audio (M3 x2, L-R x 2); Serial (D-sub 9-pin x 1); LAN (RJ-45 x 1, 10Base-T/10/100Base-TX)</b>
	<b>Audio (RCA x 2, L-R x 1); Audio monitor out (M3 x 1, L-R x 1)</b>
	<b>Composite video (RCA x 1); S-Video (Mini-DIN 4-pin x 1)</b>
	<b>PC1 (D-sub HD 15-pin x 1); PC2 in/out (D-sub HD 15-pin x 1)</b>
	<b>HDMI (19-pin x 1)</b>
<b>Replacement Lamp</b>	<b>ET-LAV200</b>
<b>Optional Accessories</b>	<b>ET-RFV200 (Replacement filter unit)</b>
<b>Optional Lens</b>	<b>--</b>
<b>Standard Accessories</b>	<b>CD-ROM software</b>
	<b>Carrying bag</b>
	<b>VGA cable</b>
	<b>Power cord</b>
	<b>Battery for remote control unit</b>
	<b>Wireless remote control unit</b>